

# Datto Managed Power

Cloud-controlled power that's efficient, reliable and simple to manage

## Product Overview

Datto Managed Power addresses the all-too-common IT challenges like expensive on-site visits, tricky troubleshooting and delayed issue resolution. It offers a streamlined, all-in-one solution to manage power from anywhere. By eliminating the need for additional hardware or software, it offers a scalable approach to remote power management.

## Advantages of Datto Managed Power

- » **Operational efficiency:** Automate rebooting of devices to reduce manual interventions and operational expenses.
- » **Reliability:** Schedule maintenance to prevent downtime and ensure continuous operation of critical IT resources.
- » **Remote control:** Take control of your power infrastructure from anywhere. Reduce dependence on physical access and enjoy greater flexibility.
- » **Energy management:** Monitor and optimize energy usage to align with sustainability goals and minimize costs.
- » **Surge protection:** Protect sensitive equipment from power surges, extending the lifespan of your IT assets.

## Key Features of Datto Managed Power

- » **Flexible hardware options:** Options include units with 6 outlets for smaller setups and 14 outlets for larger environments, providing flexibility for various IT infrastructure needs.
- » **Individual outlet metering:** Gain detailed power consumption insights for each connected device, enabling effective energy management and cost reduction.
- » **Cloud management:** Facilitate remote monitoring and management of power distribution, simplifying operations and eliminating traditional management complexities.
- » **Automated device management:** Leverage scheduled power cycles and ping monitoring for proactive management, ensuring reliability and performance.
- » **Integrated ecosystem:** Achieve a unified management experience across your IT infrastructure that is compatible with leading platforms and devices.
- » **Simple procurement and comprehensive support:** Access straightforward purchasing options and benefit from Datto's dedicated support and warranty services.



**datto** | MANAGED POWER



**DMP-PDU6R-12-515**  
6-Outlet PDU (1U)



**DMP-PDU14R-12-515**  
14-Outlet PDU (2U)

<b>Input</b>	Nominal Input Voltage	100-120V	100-120V
	Derated Maximum Input Current	12A	12A
	Input Frequency	50-60 Hz	50-60 Hz
	AC Input Connection	(1) IEC C-14	(1) IEC C-14
<b>Output</b>	Nominal Output Voltage	100-120V	100-120V
	Frequency Compatibility	50-60 Hz	50-60 Hz
	Output Receptacles	(6) NEMA 5-15R	(14) NEMA 5-15R
	Overload Protection	15A	15A
	Maximum Capacity	1440W	1440W
<b>Surge Protection</b>	Surge Suppression Energy Rating (8/20 uS)	1080J	3240J
	Protection Modes	Full Normal Mode (L-N) Common Modes (N-G & L-G)	Full Normal Mode (L-N) Common Modes (N-G & L-G)
	Maximum Continuous Operating Voltage	150V	150V
	Voltage Protection Rating (VPR)	500 V	500 V
<b>Interfaces</b>	Ethernet Port	(2) 10/100/1000Mbps RJ45  (1) Uplink Port (1) Network Pass-Through Port	(2) 10/100/1000Mbps RJ45  (1) Uplink Port (1) Network Pass-Through Port
	Reset Button	(1) Recessed button	(1) Recessed button
	Power Button	(1) Backlit Power Button	(1) Backlit Power Button
	LCD Display + Navigation Buttons	1.3" display for visualizing power information (2) Buttons for navigating display	1.3" display for visualizing power information (2) Buttons for navigating display
	<b>LED Indicators</b>	Power	-
Protected		Green	Green
Grounded		Green	Green
Outlet		Green per Outlet	Green per Outlet
Ethernet		Activity/Link	Activity/Link
<b>Main Component</b>	Metering IC	Prolific PL7413	Prolific PL7413
	CPU	Airoha EN7562	Airoha EN7562
	Flash Size	128MB SPI	128MB SPI
	Memory Size	256MB DDR3	256MB DDR3
<b>Physical Properties</b>	Dimensions (H x W x D)	1.73" x 17.32" x 2.75" (44 x 440 x 70 mm)	3.46" x 17.32" x 3.46" (88 x 440 x 88 mm)
	Form Factors Supported	Rackmount- Horizontal(1U)[Reversible] Rackmount -Vertical(0U) Wall Mount - Horizontal/Vertical Desktop	Horizontal(2U) [Reversible] Wall Mount - Horizontal/Vertical Desktop
	Included Accessories	(1) NEMA 5-15P to IEC C13 Power Cable (2) Short Rack/Wall Brackets (2) Deep Rack Brackets (8) Bracket Screws (4) Wall Mounting Screws (4) Drywall Anchors Mounting (4) Rubber Feet	(1) NEMA 5-15P to IEC C13 Power Cord (2) Short Rack/Wall Brackets (2) Deep Rack Brackets (8) Bracket Screws (4) Wall Mounting Screws (4) Drywall Anchors Mounting (4) Rubber Feet (1) Retention Clip
	Weight	2.58 lb (1.17 kg)	6.55 lb (2.97 kg)
<b>Environmental</b>	Operating Temperature	0°C to 50°C (32°F to 122°F)	0°C to 50°C (32°F to 122°F)
	Storage Temperature	-30°C to 70°C (-22°F to 158°F)	-30°C to 70°C (-22°F to 158°F)
	Humidity	5%-95% non-condensing	5%-95% non-condensing
<b>Safety Regulation</b>	Power Distribution Unit (PDU)	UL 62368-1 + CSA C22.2 no. 62368-1 UL1449 ed5	UL 62368-1 + CSA C22.2 no. 62368-1 UL1449 ed5
	EMC Emissions (USA, Canada)	FCC Part 15 Subpart B / ICES-003 Issue 7 (Class B) IEC 61000-4-2	FCC Part 15 Subpart B / ICES-003 Issue 7 (Class B) IEC 61000-4-2
	ESD Protection	Contact: Level 3 Air: Level 3	Contact: Level 3 Air: Level 3
	Surge Protection	0°C to 50°C (32°F to 122°F)	0°C to 50°C (32°F to 122°F)



**Corporate Headquarters**

Kaseya Miami  
701 Brickell Avenue  
Suite 400  
Miami, FL 33131  
partners@datto.com  
[www.datto.com](http://www.datto.com)

**Global Offices**

USA: 888.294.6312  
Canada: 877.811.0577  
EMEA: +44 (0) 118 402 9606  
Australia: +61 (02) 9696 8190  
Singapore: +65-31586291

Copyright © 2024 Datto, Inc.

All rights reserved.  
Effective April 2024..

All information is accurate to the best of Datto's knowledge at the time prepared. Datto reserves the right to correct errors/discrepancies.